

Using One Drive

Setup One Drive

- Start configuring OneDrive in RClone by running the config command.

```
# rclone config
```

- You will be prompted with configuration options. Choose n to create a new remote.

```
No remotes found - make a new one
n) New remote
s) Set configuration password
q) Quit config
n/s/q> n
```

- Enter for instance "UL-OneDrive" as the name for the remote.

```
name> UL-OneDrive
```

- For storage type enter "onedrive".

```
Type of storage to configure.
Enter a string value. Press Enter for the default ("").
Choose a number from below, or type in your own value
...
21 / Mega
    \ "mega"
22 / Microsoft Azure Blob Storage
    \ "azureblob"
23 / Microsoft OneDrive
    \ "onedrive"
24 / OpenDrive
    \ "opendrive"
25 / Openstack Swift (Rackspace Cloud Files, Memset Memstore, OVH)
    \ "swift"
...
Storage> onedrive
** See help for onedrive backend at: https://rclone.org/onedrive/ **
```

- Leave client_id and client_secret empty. Press enter to leave the fields blank.

```
Microsoft App Client Id
Leave blank normally.
Enter a string value. Press Enter for the default ("").
client_id>
Microsoft App Client Secret
Leave blank normally.
Enter a string value. Press Enter for the default ("").
```

```
client_secret>
```

```
* Do not go for advanced config, type n
```

```
Edit advanced config? (y/n)
```

```
y) Yes
```

```
n) No (default)
```

```
y/n> n
```

- Press y to use auto configuration.

```
Remote config
```

```
Use auto config?
```

```
* Say Y if not sure
```

```
* Say N if you are working on a remote or headless machine
```

```
y) Yes (default)
```

```
n) No
```

```
y/n> y
```

- A browser window will open to a Microsoft login screen. Login using your ULCN account information.
- When prompted for config_type choose "onedrive", type 1.

```
Choose a number from below, or type in an existing value
```

```
1 / OneDrive Personal or Business
```

```
\ "onedrive"
```

```
2 / Root Sharepoint site
```

```
\ "sharepoint"
```

```
3 / Type in driveID
```

```
\ "driveid"
```

```
4 / Type in SiteID
```

```
\ "siteid"
```

```
5 / Search a Sharepoint site
```

```
\ "search"
```

```
Your choice> 1
```

- You'll be prompted to connect to the root of your OneDrive. Press y to continue.

```
Found 1 drives, please select the one you want to use:
```

```
0: OneDrive (business) id=b!9lLca7qW5Uqos5tnc3zl3xVQs7GKhd1Pi_6ugA5eVjVYitM-  
xxxxxxxxxxxxxxxx
```

```
Chose drive to use:> 0
```

```
Found drive 'root' of type 'business', URL:
```

```
https://leidenuniv1-my.sharepoint.com/personal./deuler_vuw_leidenuniv_nl/Doc  
uments
```

```
Is that okay?
```

```
y) Yes (default)
```

```
n) No
```

```
y/n> y
```

* Press y to confirm that the remote is ok.

```
-----
[UL-OneDrive]
type = onedrive
token = {"access_token":"xxx...xxx"}
drive_id = b!9lLca7qW5Uqos5tnc3zl3xVQs7GKhd1Pi_6ugA5eVjVYitM-xxxxxxxxxxxxx
drive_type = business
-----
y) Yes this is OK (default)
e) Edit this remote
d) Delete this remote
y/e/d> y
```

- Press q to close the remote configuration procedure.

Current remotes:

```
Name                Type
====                ====
UL-OneDrive         onedrive

e) Edit existing remote
n) New remote
d) Delete remote
r) Rename remote
c) Copy remote
s) Set configuration password
q) Quit config
e/n/d/r/c/s/q> q
```

- Create a "OneDrive" directory in your home folder to mount the remote that you just created.

```
mkdir ~/OneDrive
```

- Mount the remote by using the command:

```
rclone --vfs-cache-mode writes mount UL-OneDrive: ~/OneDrive &
```

And now the drive is mounted:

```
# df ~/OneDrive
Filesystem      1K-blocks  Used  Available Use% Mounted on
UL-OneDrive:    1073741824 2952 1073738868  1% /home/deul/OneDrive
```

From:

<https://helpdesk.strw.leidenuniv.nl/wiki/> - **Computer Documentation Wiki**

Permanent link:

<https://helpdesk.strw.leidenuniv.nl/wiki/doku.php?id=linux:onedrive&rev=1705433358>

Last update: **2024/01/16 19:29**



